

# Certificate of constancy of performance

No. 0672-CPR-0699

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the

Construction Product(s)

Pot Bearing with trade name MAURER Pot Bearing

placed on the market under the name or trade

mark of

Maurer SE

Frankfurter Ring 193

80807 München

Germany

produced in the manufacturing plant(s)

Maurer SE

Frankfurter Ring 193

80807 München

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

Annex ZA

of the standard(s)

EN 1337-5:2005

under system

1

for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

#### constancy of performance of the construction product.

This certificate was first issued on **2017-04-03**, replaces the EC-Certificate of Conformity (0672-CPD-005.3) to a certification issued on 2006-12-11 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

This document has been translated for informative purpose only. Original version is issued in German. In any case of doubt the German version is valid.



Dipl.-Ing. Siegfried Gerber

DAKKS

Deutsche
Akkreditierungsstelle
D-ZE-11016-01-00

Head of Certification Body

### Annex 1

to the certificate of constancy of performance No. 0672-CPR-0699

Main performances for the construction product

## Pot Bearing

with trade name

## **MAURER Pot Bearing**

with elastomeric pad of compound MEN LD1 and internal seal of brass or of PTFE/carbon as fixed bearing or with horizontal sliding part, types 2.1 to 2.3 in accordance with EN 1337-1, for effective bearing temperatures of -35°C to +48°C as sliding bearing and of -40°C to +50°C as fixed bearing, for use in building and civil engineering works where requirements on individual bearings are critical,

This Annex is only valid together with the certificate of constancy of performance according EU-BauPVO 0672 – CPR – 0699

